



11001

PRODUCT:	TERRACOTTA SEALER GLAZE	Code: TGW
-----------------	--------------------------------	------------------

DESCRIPTION

A water based 100% Acrylic Sealer / Glaze finish for cleaned, non-glazed Terracotta clay roof tiles to seal against the penetration of water from rain and dew and to restrict the growth of disfiguring algae and lichen. The sealer dries to a pleasing semi-glaze sheen which highlights the natural colour of the tile..

SUNBOND TERRACOTTA TILE SEALER GLAZE is water based with little odour and is environment friendly.

PROPERTIES

Gloss level	Conforms to AS 2311 - Semi Gloss
Exterior durability	Very Good
Colour	Clear
Coverage	Varies with surface (eg 8-8sq M/L)
Number of Coats	2 light coats recommended
Recoat time	2 hours in normal conditions
Thinning	not normally necessary.
Clean Up	Water

Surface Preparation

Water blast and clean tiles using a 3,000psi machine. Ensure all dirt, fungus, and other deposits are fully removed. Give attention to effective cleaning of the noses of tiles, taking care to not force water up under toiles onto ceilings or soffits. Ingrained fungi and organic material may need to be bleached before coating. Sodium hypochlorite (Pool Chlor or Hypo) is normally used with particularly difficult spots, sometimes requiring treatment with caustic soda. SODIUM HYPO CHLORITE AND CAUSTIC SODA ARE CONCERNTRATED AND CORROSSIVE CHEMICALS AND MUST BE HANDLED ACCORDING TO THEIR MANUFACTURERS SAFETY DIRECTIONS. Applicators should be trained in the proper use of these substances for the treatment of roofs

Previously Painted Surfaces.

Not applicable

Application

Apply two coats by airless spray.

OTHER INFORMATION

Stir before use. Surface must be dry before application. Do not apply at surface temperatures below 10 degrees Celsius. This coating is not recommended for application to previously glazed tiles (gloss or low sheen) unless fully removed nor to brown or dark coloured terra cotta tiles